

## COGENERATION GAS GENSET G.E. 8291 SRG 75

### NATURAL GAS

1500 rpm			1800 rpm		
100%	75%	50%	100%	75%	50%

#### Generating set performance

Peak efficiency net rated output	400		-		kVA
Peak efficiency net active power output at 0,8 p.f.	320		-		kW
Lean burn net rated output (*)	380		-		kVA
Lean burn net active power output at 0,8 p.f.	305		-		kW
Voltage available (L - L)	190 to 440		190 to 480		V

(\*) According to TA-Luft emissions rule

#### Prime mover performance

Peak efficiency power	342	257	172	-	-	-	kW
Lean burn power	321	241	162	-	-	-	kW
Mean piston speed	6,5		7,8				m/s

#### Derating

(see general genset installation manual)

#### Prime mover data

Type	Four stroke cycle	
Induction type	TCA air / water	
Cylinders, number and arrangement	12V	
Bore x Stroke	145 x 130	mm
Total displacement	25,8	l
Exhaust manifold pattern	wet	
Speed governor	electronic	
Max speed drop steady conditions	isochronous	
Engine rotation mass moment of inertia (less flywheel)	2,12	kgm <sup>2</sup>
Moment of inertia of flywheel	3,51	kgm <sup>2</sup>
Engine rotation (viewed facing flywheel)	CCW	
Compression ratio	11:1	

#### Lubrication system

Total lube oil capacity (including filters)	~71,5	l
Oil sump capacity:	min	~44
	max	~60,5
Lube oil specifications	see Technical Data	
Maximum oil temperature	120	°C
Minimum oil pressure at rated speed	2,94	bar
Max Specific lube oil consumption	0,7% max of gas consumption	

1500 rpm			1800 rpm		
100%	75%	50%	100%	75%	50%

## Intake and exhaust system

Maximum allowable intake restriction with clean air filter	250		mmH <sub>2</sub> O
Maximum allowable intake restriction with dirty air filter	500		mmH <sub>2</sub> O
Air filter type	dry, paper cartridge		
Maximum allowable back pressure in exhaust system	500		mmH <sub>2</sub> O
Charge pressure (peak efficiency)	0,51	-	bar
Charge pressure (lean burn)	0,64	-	bar

## Carburation

Venturi based air/gas mixer and zero pressure governor.  
Interfaceable with automatic lambda control system

## Ignition

Digital, single firing  
On request interfaceable with knocking control system

## Electric system

Breakaway current	1670	A
Cranking motor rating	6	kW
Minimum recommended battery capacity	2 x 150	Ah
Auxiliary voltage	24	V
Alternator with voltage electronic control unit (negative earth)	28V, 30A	
Terminal connection board	Standard	

## Cooling system

Coolant capacity (engine only)	~100	l
Max engine return jacket water temperature	75	°C
Max engine outlet jacket water temperature (alarm)	98	°C
Minimum allowable jacket water coolant flow	46	m <sup>3</sup> /h
Water pressure drop in the jacket water coolant circuit at minimum coolant flow	1,3	bar
Minimum allowable water coolant flow to intercooler	21	m <sup>3</sup> /h
Max inlet water temperature to intercooler	54	°C
Max inlet water temperature to oil cooler	80	°C

1500 rpm			1800 rpm		
100%	75%	50%	100%	75%	50%

### Synchronous generator data

Poles	4	
Phases	3 + N	
Standard winding connections	STAR	
Windings treatment	for humide and saline climates	
Stator/rotor impregnation	class H	
Temperature rise	according to class H	
Frame mounting	B3-B14	
Enclosure (according to IEC 34-5 Standards)	IP21	
Cooling	air	
Damper windings	for parallel (optional)	
Maximum overspeed	2250	min <sup>-1</sup>
Waveform distortion	no more than 5%	
Overexcitation device	for I <sub>cc</sub> >3I <sub>n</sub> (optional)	
Exciter	brushless rotating exciter design with solid state	
Voltage regulator	static electronic design	
Steady voltage precision	within ± 1% V <sub>n</sub> from no load to full at 0,8 ÷ 1 p.f.	%

### Basic data

Installation dimensions (width x length x height)	1340 x 3695 x 2070	mm
Dry weight (with standard accessories)	~4160	kg
Wet weight (with standard accessories)	~4330	kg

### Electric control board (only on request)

The manual starting control panel has been designed and built to combine all the instruments control and warnings lights both for the engine and the generator.

The sheet steel made panel is carefully painted for tropical climate and is designed for generator mounting and dust proof application. The main equipments included on the control panel are the following: three ammeters with CT's; voltmeter; voltmeter selector switch; frequency meter; moulded case triple-pole circuit breaker with thermal and magnetic releases and minimum voltage coil; electronic device for shut-down of the engine in case of HWT, LOP and overspeed; starting key and stop push button; acoustic signal; warning light for: high cooling water temperature, low oil pressure, high oil temperature, battery charging, overspeed, low and high gas pressure, high supercharged air temperature; outlet power cable terminal box; hours meter; instruments for: water temperature, oil temperature, oil supercharged air pressure, exhaust temperature, water temperature outlet to oil cooler.

1500 rpm			1800 rpm		
100%	75%	50%	100%	75%	50%

### Heat balance (Peak efficiency) (§)

Input energy (LHV)	936(100)	737(100)	551(100)	-	-	-	kW (%)
Work	342(37)	257(35)	172(31)	-	-	-	kW (%)
Heat to coolant (water + oil)	346(37)	295(40)	251(46)	-	-	-	kW (%)
Heat to exhaust (LHV)	209(22)	158(21)	107(19,5)	-	-	-	kW (%)
Heat to intercooler	14,1(1,5)	5,7(1)	3(0,5)	-	-	-	kW (%)
Heat to radiation	24(2,5)	22(3)	18(3)	-	-	-	kW (%)
Heat to exhaust cooled to 140 °C	144	108	74	-	-	-	kW
Max exhaust temperature (after turbine)	390	382	369	-	-	-	°C
Exhaust gas flow	1614	1225	889	-	-	-	kg/h
Induction air flow	1198	909	658	-	-	-	m <sup>3</sup> N/h
SFC - Specific fuel consumption	9,8	10,3	11,5	-	-	-	MJ/kWh
BMEP	10,6	8	5,3	-	-	-	bar

### Heat balance (Lean burn) (§)

Input energy (LHV)	946(100)	742(100)	536(100)	-	-	-	kW (%)
Work	321(34)	241(33)	162(30)	-	-	-	kW (%)
Heat to coolant (water + oil)	344(36)	300(40)	241(45)	-	-	-	kW (%)
Heat to exhaust (LHV)	234(25)	179(24)	121(23)	-	-	-	kW (%)
Heat to intercooler	22,6(2,5)	8,5(1)	2,8(0,5)	-	-	-	kW (%)
Heat to radiation	23,9(2,5)	14,3(2)	8,8(1,5)	-	-	-	kW (%)
Heat to exhaust cooled to 140 °C	160	122	80	-	-	-	kW
Max exhaust temperature (after turbine)	390	386	358	-	-	-	°C
Exhaust gas flow	1842	1419	1025	-	-	-	kg/h
Induction air flow	1374	1057	764	-	-	-	m <sup>3</sup> N/h
SFC - Specific fuel consumption	10,6	11,1	11,9	-	-	-	MJ/kWh
BMEP	9,95	7,47	5,02	-	-	-	bar

(§) Indicative average figures depending on installation, setting of speed regulator and carburetor